




Insert Part Number	3520-2.20X1.0DSLIR
Insert Thread Form	Metric Coarse
Nominal Thread Size	M2.2 X 0.45
Insert Length Q (installed)	D 1.0D
Insert Length Q (installed)	mm 2.200
Insert Material	304 Stainless Steel
Insert Coating/Plating	-
Military Standard	# MA3329-100
National Aerospace Standard	#
Federal Stock	# -
National Stock / NATO	# -

Optimum thread performance with Wire Thread Inserts is achieved when the inserts are installed 1/2 to 1 pitch below the surface of the tapped hole. This means that the actual length of an installed insert is equal to dimension Q less 1/2 to 1 pitch. Dimensions S and T allow for tap end clearance of intermediate taps. When using Bottoming and Spiral Flute Taps these dimensions maybe reduced by an amount equal to 2 thread pitches. Any countersink depths must be added to these dimensions.

COMPATIBLE POWERCOIL INSTALLATION AND REMOVAL TOOLS		
TOOL TYPE	Part #	
Hand Installation Tool	-	
Tang Break Tool	3500-TB2	
Removal Tool	3500-RT1	
Machine Installation Tool	3520-2.20MIT	
Mandrel Installation Tool	-	
Captive Prewinder Tool	3520-2.20HIP	
Non-Captive Prewinder Tool	-	
Spring Loaded tang Break Tool	3500-STB1	
Pneumatic Front end assembly (FEA)	3520-2.20MIP	
FEA Mandrel	3520-2.20MIPM	
FEA Nozzle	3520-2.20MIPN	
Pneumatic Tool	3500-MIP1	

powercoil.com.au

PowerCoil is a registered trademark of Bordo International Pty Ltd Australia



DRILLED HOLE DIMENSIONS INTERMEDIATE/PLUG TAP

Drill Size	mm	2.30
Drill Part Number		2007-2.30
Drill Size inch	inch	#42
Drill Part Number inch		2013-42
A Minor Diameter minimum	mm	2.297
A Minor Diameter maximum	mm	2.397
S Drilling Depth minimum	mm	4.23

TAPPED HOLE DIMENSIONS

Tap Size	STI	M2.2 X 0.45
Tap Size	-	-
B Major Diameter	mm	2.785
C Pitch Diameter MIN	mm	2.492
C Pitch Diameter MAX	5H mm	2.532
C Pitch Diameter MAX	6H mm	2.547
T Tapping Depth MIN	mm	3.78
Power Coil Tap Part Number	STI Taper	3520-2.20T
Power Coil Tap Part Number	STI Intermediate	3520-2.20I
Power Coil Tap Part Number	STI Bottoming	3520-2.20B
Power Coil Tap Part Number	STI SpiralPoint	3520-2.20SP
Power Coil Tap Part Number	STI SpiralFlute	3520-2.20SF

INSERT SPECIFICATIONS

E Fitted Minor Diameter	mm	1.713
Q Nominal Length Installed	mm	2.200
Free Coil Diameter minimum	mm	2.757
Free Coil Diameter maximum	mm	3.000
Free Coils minimum	#	2.90
Free Coils maximum	#	3.20

IMPORTANT The success of any drilling and tapping operation is dependant upon many factors - type of material being cut, cutting speed, coolant, equipment being used - and it is not possible to give specific drill sizes for each material. Drill sizes shown are recommendations only and PowerCoil would strongly suggest that independent testing be performed for specific and critical applications.

When using wire thread inserts it is important that the drilling and tapping diameters and lengths shown are adhered to.

The figures outlined in these tables encompass effective free coil tolerances for most globally recognized standards and manufacturers, including those of reduced diameter wire thread inserts.

Number of Free Coils – the number of coils on an un-installed insert counted along the insert length 90° from the tang.

