



Insert Part Number		3721-24.00HD
Military Specification		-
Reference Number		KNHM 24X2.0
Insert Type		Heavy Duty
Internal Thread Form		Metric Fine
Internal Thread Size		M24 X 2
External Thread Size		M33 X 2
Nominal Length Q	mm	33.00
Insert Material		Stainless Steel - 303 CRES
Insert Finish		Passivated
Insert Coating		-


Loksert solid keylocking inserts are an easily installed thread assembly that are ideal for replacing damaged or worn threads in virtually any material - ferrous, non-ferrous and non-metallic.

They are constructed from high quality carbon steel or extremely hard wearing stainless steel. One piece Loksert inserts are supplied with the dove-tailed locking keys pre-assembled. The pre-positioned keys automatically position the insert at the correct depth below the surface of the parent material. Lokserts are suitable for repairing and creating threads in a wide range of applications including forgings and castings and are especially suited to situations that experience heavy wear and vibration - such as mining, construction and earthmoving equipment.

COMPATIBLE LOKSERT INSTALLATION AND REMOVAL TOOLS	
TOOL TYPE	Part #
Hand Installation tool - Miniature	-
Hand Installation tool - Thin Wall	-
Hand Installation tool - Heavy Duty	3600-24.00HT
Hand Installation tool - Universal (TW & HD)	-
Hand Installation tool - Extra Heavy Duty	-
Hand Installation tool - Solid	-
Pneumatic Front End Assembly (FEA)	-
Pneumatic Tool	-

powercoil.com.au

PowerCoil and Loksert are registered trademarks of Bordo International Pty Ltd Australia





DRILLED HOLE DIMENSIONS INTERMEDIATE/PLUG TAP

A Tapping Drill Size	mm	31.00
A Tapping Drill Size	inch	-
Tapping Drill Part Number		3620-31.00*




TAPPED HOLE DIMENSIONS

Tap Size		M33 X 2
Tap Tolerance		6H
T Tapping Depth minimum	mm	37.50
T Tapping Depth minimum	inch	-
Loksert Tap Part Number	Intermediate	3621-33.00I
C Countersink Width minimum	mm	33.25
C Countersink Width minimum	inch	-




INSERT SPECIFICATIONS

Internal Thread		M24 X 2
Internal Thread Tolerance		5H
External Thread		M33 X 2
External Thread Tolerance		4h
Q Nominal Length	mm	33.00
Locking Keys	#	4



INSERT REMOVAL SPECIFICATIONS

R1 Drill Size	mm	28.75
R1 Drill Size	inch	-
R2 Drill Depth minimum	mm	6.35
R2 Drill Depth minimum	inch	-



For detailed removal instructions please visit powercoil.com.au